



3600 cfm Airblast Aftercooler

When controlled delivered air temperature is a requirement, Airpac Rentals can provide a range of air blast aftercoolers capable of cooling the discharge air to 10°C above ambient.

Airpac Rentals aftercoolers meet flow requirements to 102m³/min (3600 cfm) with pressures up to 24 bar (350 psi).

When supplied as a package with high pressure air compressors and boosters they are ideal for use in pipeline dewatering, drying and testing projects.

Technical Specifications

3600 cfm Airblast Aftercooler

Performance

Model	3600 cfm Airblast Aftercooler
Volume	3600 cfm 102m ³ /min
Working Pressure	350 psi 24 bar
Discharge Temperature	Ambient +10°C
Inlet / Outlet Connection	4" fig 206

Weights & Dimensions

	Metric	Imperial
Overall Length	2500mm	98"
Overall Width	1860mm	73"
Overall Height	2500mm	98"
Weight	3000 Kgs	6614 lbs

N.B. Weights and dimensions are for guidance only; please contact your local Airpac Rentals office for individual asset details

E. & O.E.

© Airpac Rentals 2021
A division of Vp plc



Airpac Rentals UK is certified to
BS EN ISO 9001:2015 & BS EN ISO 14001:2015



Supplier No. 10044388

UK & Europe
e: airpac.europe@vpplc.com

Asia
e: airpac.asia@vpplc.com

Australia
e: airpac.australia@vpplc.com

Middle East & Africa
e: airpac.mea@vpplc.com

Americas
e: airpac.americas@vpplc.com

09.11.21