



## 2300 psi Zone II Joy WB12 Booster Compressor

The Airpac Rentals range of Zone II (certified for open deck hazardous area operation) booster compressors are constructed to safely compress air, natural gas or nitrogen and can be operated in either a single or double stage configuration.

The WB12 Joy Zone II range offers pressure capabilities up to 159 bar (2300 psi) and volumes to 107.6m<sup>3</sup>/min (3800 cfm). Fitted with either battery or pneumatic start, stainless steel spark arrestors and overspeed protection.

An Emergency Shutdown System is also fitted to all models, enabling instant shutdown from the drill floor in the event of gas detection or similar hazards.

The unit is constructed in a four point lifting frame, designed to meet the rigours of high pressure application operations.

### Features

- Choke for total compressed medium control
- Reduced vibration through the incorporation of additional fly-wheel and pulsation dampers
- Auto lubrication to both engine and compressor ensuring continuous operation
- Exhaust cooler
- Spark arrestors
- Low oil pressure shutdown engine & air end
- Engine overspeed
- Excessive vibration shutdown
- High coolant temperature shutdown engine & air-end joint coolant system
- High exhaust temperature shutdown
- High water level inlet scrubber bottles shutdown
- High discharge temperature shutdown on both discharge scrubbers
- Low lubricator fluid level shutdown
- ESD and Emergency stop

### Options

- Experienced personnel providing a complete operational package including: hook-up & commissioning, servicing, re-fuelling and multiple installation assistance
- Hard delivery pipe
- Multiple output connections
- Delivered air oil filtration
- Interstage drying dewpoint -40°C

# Technical Specifications

## 2300 psi Zone II Joy WB12 Booster Compressor

### Performance

Model	2300 psi Joy WB12 Booster
Delivered Flow - Single Staging	3800 cfm 107.6m <sup>3</sup> /min
Delivered Pressure - Single Staging	900 psi 62 bar
Delivered Flow - Double Staging	2400 cfm 68.49m <sup>3</sup> /min
Delivered Pressure - Double Staging	2300 psi 159 bar
Discharge Temperature	Ambient +10°C
Fuel Consumption	127 litres per hour (at max. pressure)
Fuel Tank Capacity	115 litres
Max. Working Ranges	-10°C to +50°C
Outlet Connection	2" Weco 1502
Outlet Valve	3" Flanged to Weco 1502
Framed / Containerised	Framed

N.B. All figures based on 325 psi suction pressure

### Weights & Dimensions

	Metric	Imperial
Overall Length	6000mm	236"
Overall Width	2600mm	102"
Overall Height	2450mm	96"
Weight (Gross)	16,100 Kgs	35,495 lbs

N.B. Weights and dimensions are for guidance only; please contact your local Airpac Rentals office for individual asset details

E. & O.E.

© Airpac Rentals 2021  
A division of Vp plc



Airpac Rentals UK is certified to  
BS EN ISO 9001:2015 & BS EN ISO 14001:2015



**UK & Europe**  
e: [airpac.europe@vpplc.com](mailto:airpac.europe@vpplc.com)

**Asia**  
e: [airpac.asia@vpplc.com](mailto:airpac.asia@vpplc.com)

**Australia**  
e: [airpac.australia@vpplc.com](mailto:airpac.australia@vpplc.com)

**Middle East & Africa**  
e: [airpac.mea@vpplc.com](mailto:airpac.mea@vpplc.com)

**Americas**  
e: [airpac.americas@vpplc.com](mailto:airpac.americas@vpplc.com)

23.11.21