



750 - 1200 cfm (350 psi) Multi Pressure Desiccant Dryer

If high quality clean dry compressed air is a process or project requirement, Airpac Rentals can provide a range of desiccant dryers sized to meet their primary compressor fleet.

The unit processes air volumes of 21.2m³/min (750 cfm) to 34m³/min (1200 cfm) to pressures ranging from 7 bar (100 psi) to 24 bar (350 psi).

Mounted in a certified lifting frame for transport and protection, Airpac Rentals desiccant dryers are a complete package, incorporating:

- A twin tower heatless adsorbent dryer unit
- Integral aftercooler with condensate separator and auto drain
- Double oil removal filtration with auto drains and final dust filter

Options

- 2 inch air hoses
- Use of additional aftercoolers

Technical Specifications

750 - 1200 cfm (350 psi) Multi Pressure Desiccant Dryer

Performance

Model	7 bar	24 bar
Volume Dependent on Working Pressure	750 cfm @ 100 psi 21.2m ³ /min @ 7 bar	1200 cfm @ 350 psi 34m ³ /min @ 24 bar
Residual Oil Content @ 20°C	0.03mgs/m ³	
Discharge Temperature	Ambient +10 °C	
Pressure Dewpoint	-40°C	
Inlet / Outlet Connections	2" Fig 100 Weco Union	

Weights & Dimensions

	Metric	Imperial
Overall Length	4180mm	165"
Overall Width	1580mm	62"
Overall Height	3120mm	123"
Weight	4500 Kgs	9921 lbs

N.B. Weights and dimensions are for guidance only; please contact your local Airpac Rentals office for individual asset details

E. & O.E.

© Airpac Rentals 2021
A division of Vp plc



Airpac Rentals UK is certified to
BS EN ISO 9001:2015 & BS EN ISO 14001:2015



Supplier No. 10044388

UK & Europe
e: airpac.europe@vpplc.com

Asia
e: airpac.asia@vpplc.com

Australia
e: airpac.australia@vpplc.com

Middle East & Africa
e: airpac.mea@vpplc.com

Americas
e: airpac.americas@vpplc.com

24.11.21