

Sand Collection Box



Airpac Rentals
Energy Industry Solutions



Sand Collection Box

Sand collection box and filtration system for use in conjunction with Airpac Rentals sand filtration units.

Two screens are positioned at the front of the sand box so the rejected product from the sand filtration unit can be separated.

Sand is filtered from the water and easily removed by the operator, the recovered water can then be removed.

Features

- Standard 200 Micron screens supplied
- DNV 2.7-1 lifting specification
- 2" 1502 inlet connection
- 2" 206 Weco outlet
- Vented Flame Arrestor

Options

- A range of Micron screens ranging from 50 - 800 Micron are available on request

Technical Specifications

Sand Collection Box

Performance

Model	Sand Collection Box
Filter Mesh	Standard 2 x 200 Micron screens
Inlet Connection	2" x 1502 Weco Union
Outlet Connection	2" x 206 Weco Union
Flush Line Hose	2" 1502 M/F Weco Union Length 15 meters MWP 580 psi
Lifting Certification	DNV 2.7-1
Forklift Pockets	Yes
Flame Arrestor	2" Flame Arrestor fitted to vent

Weights & Dimensions

	Metric	Imperial
Length	1732mm	68"
Width	1902mm	75"
Height	1413mm	56"
Weight	1100 Kgs	2425 lbs

N.B. Weights and dimensions are for guidance only; please contact your local Airpac Rentals office for individual asset details

E. & O.E.

© Airpac Rentals 2021
A division of Vp plc



Airpac Rentals UK is certified to
BS EN ISO 9001:2015 & BS EN ISO 14001:2015



UK & Europe
e: airpac.europe@vpplc.com

Asia
e: airpac.asia@vpplc.com

Australia
e: airpac.australia@vpplc.com

Middle East & Africa
e: airpac.mea@vpplc.com

Americas
e: airpac.americas@vpplc.com

25.11.21